IP65

LYSTER PAR 1920

FC

NEXSTRALE

LYSTER PAR 1920

FC

Light Source
19*20W RGBL+WW+CW

Angle:
Beam angle: 25°
Field Angle: 50°

Color Temperature
1700K - 20000K

Weight
3.5KG

SOURCE

19*20W RGBL+WW+CW
50,000 Hour Average LED Life

PHOTOMETRIC DATA

CRI :>90,TLCI>90
PMMA lens,42mm
Beam Angle: 25°
Field Angle: 50°
EFFECTS
Variable Strobe Rate: 1- 20kHz
Auto,manual color,CTO,color fading
Variable 16-bit Dimming Modes and Curves
Halogen dimming curve
Mode Options

COLOR

Red,Green,Blue,Lime, Warm White, Cold White
Variable CCT 1700K - 20000K

ELECTRICAL/THERMAL

AC 100-240V - 50/60Hz
240W Max Power Consumption
-20°C to 45°C

CONTROL CONNECTIONS

5 DMX Channel Modes (2/6/8/14/21CH)
Manual and DMX Controlled Dimmer and Color
4 Button Control Panel, LED Display
RDM (Remote Device Management)
USB port support Wireless DMX and APP control
5pin DMX and IP20 Locking Power Cable In/Out
SIZE / WEIGHT (Without Accessories)
Length: 185mm
Width: 114mm
Vertical Height: 114mm
Weight: 3.5KG

OTHERS

Floor Stand/ Yoke
RGBL+WW+CW

LED technology · DMX · Stand-alone mode · Master / Slave
Strobe effect · RGBW · Linear CTO · Flicker-free

NEXSTRALE